

INSTALLATION INSTRUCTION

32102

IMPORTANT:

FOR A SAFE AND SECURE INSTALLATION, THESE FIXTURES MUST BE INSTALLED BY MEANS OF SUPPORTS THAT ARE INDEPENDENT OF THE OUTLET BOX.

HANGING THE FIXTURE

1. Shut off the power at the circuit breaker and removed old fixtures from ceiling, including the old crossbar.
2. Carefully unpack new fixture and lay all the parts on a clear surface.
3. Thread nipple into coupling tight with hex nut.
4. Put center column over nipple and secure with fixture loop.
5. Thread nipple into coupling tight with hex nut, place caps and tube over nipple and secure with washer and hex nut.
6. Place glass over nipple and secure with washer and hex nut.
7. Place decorative cap and small cap over nipple and secure with finial.
8. Place glass shield over studs on support plate and secure with rubber washer and knurled knobs.

CONNECTING THE WIRES

9. Take the black wire from the ceiling junction box and the smooth wire leg from the fixture and twist bare ends together. Twist wire connector onto the end of wires until snug.
10. Repeat same process with white junction box white and ribbed wire leg of fixture wire. **NOTE:** Twist wires together in the same direction as you twist the wire connector onto wires.
11. If your junction box has a grounding wire (green or bare copper), attach this wire and the bare copper wire from the fixture. If junction box has no ground wire, attach the bare copper fixture wire to the junction box with a screw.
12. Tuck these wire connections neatly into the ceiling outlet box and then raise the canopy all the way to the ceiling. Thread onto ceiling loop protruding through canopy.
13. Install the light bulbs in accordance with the fixtures specifications.

NOTE: DO NOT EXCEED THE SPECIFIED WATTAGE.

Your installation is now complete. Return power to the junction box and test the fixture.

